



SLATS

69 SLATS



The pool protection that makes a splash



SLATS

OPAQUE PVC 69 SLATS

THE SLATS THAT KEEP YOUR POOL SAFE
WITH EASE

+ DESIGN

- Perfect finish thanks to a weld-free and burr-free end-cap.
- No brush.
- Reduced rolling diameter on the cover tube.

+ DURABILITY

- Increased health protection thanks to the absence of lead compounds.
- Long-lasting against stains, organic deposits and UV rays.
- Resistance to ageing in accordance with standard requirements NF T 54 405-1: 2013.



Our custom-made slats fit your pool shape to perfection.

A choice of 4 colours

DEL opaque PVC 69 slats comply with the standard NF P90-308* and are compatible with all types of pool covers (in-ground, above-ground and mobile).



White

Beige

Grey

Blue



For an above-ground cover equipped with opaque PVC 69 slats, white is the most preferable colour in very sunny regions.
* To comply with safety standard NF P90-308, the cover made of opaque PVC 69 slats must be at least 2.00 m wide.

SLATS

SOLAR POLYCARBONATE SLATS

ULTRA-RESISTANT SLATS
THAT HEAT YOUR POOL WATER

+ AESTHETICS

- Perfect finish thanks to a weld-free and burr-free end-cap.
- No brush.
- Reduced rolling diameter on the cover tube.

+ ROBUSTNESS

- Extreme shock resistance.
- Watertightness maintained in the event of hailstones up to 4 cm (size of a golf ball).
- Cover opening and closing maintained after the fall of 5 cm hailstones (size of an egg).
- Increased health protection thanks to the absence of lead compounds.
- Long-lasting against stains, organic deposits and UV rays.
- Resistance to ageing in accordance with standard requirements NF T 54 405-1: 2013.

+ HEATED WATER

- Slats acting as genuine solar collectors to heat the water.
- Reduced use of the heat pump.



Our custom-made slats align perfectly with the edges of your pool.

A range of 7 colours

DEL solar polycarbonate slats comply with the standard NF P90-308* and are compatible with all types of pool covers (in-ground, above-ground and mobile).



Absolute black

Crystal black

Silver

Crystal blue

Crystal

Crystal brown

Crystal green



* To comply with safety standard NF P90-308, the cover made of solar polycarbonate slats must be at least 2.00 m wide.

Your safety locking kit Pushlock

Aesthetic and discreet, the strap is clipped into the Pushlocks located on the width(s) of the pool, ensuring its safety.



White



Beige



Blue



Light grey



Dark grey



Argile green

Read carefully and keep for future reference.

The slats are parts of the slatted cover designed to prevent children under 5 years of age from accessing the pool. This product complies with the NF P90-308 standard. It is no substitute for common sense or individual responsibility. It is not intended either to be a substitute for parental and/or adult supervision, which is the essential factor for the protection of young children. A child can get drowned within less than 3 minutes; no type of protection will ever replace the vigilance and supervision of responsible adults.

Warranty: 3 years for opaque PVC 69 slats and 5 years for solar polycarbonate slats, in accordance with our general sales terms.

Order form: to have slats correctly adjusted to the pool, it is essential to provide a drawing of the pool with measurements taken every 1 meter. In accordance with the NF P90-308 standard, the gap between the inside of the pool and the edge of the cover must be less than 70 mm.

Use: for all seasons. For a proper functioning, maintain a constant water level corresponding to a normal filtration of the pool. It is essential to have a water level regulator. The water level has to comply with the technical notice. Solar polycarbonate slats are incompatible with bromine treatments.

Use limits: DEL automatic slatted covers on overflowing pools can only be compliant if the pool is fitted with a device such as the Infinity control box that automatically lowers the water level by at least 2 cm when the cover is closed on the pool. To date, DEL automatic slatted covers with a removable form on a side staircase do not comply with French standard NF P90-308. Unless otherwise specified by the manufacturer, immersion alarms are not compatible with DEL automatic slatted covers.

Wintering: the swimming pool must be wintered on the basis of its geographical location. Without lowering the water level, close the cover to its safety position and where applicable install a wintering net to protect the cover. If the water level is lowered so that the wall units are above the waterline, roll the cover in and secure the pool using a winter safety cover.

Packing list: for a swimming pool measuring 5.00 x 10.00 m. Slats: 5 packages: 5.10 x 0.25 x 0.20 m - 250 kg.

Manufacturer: DEL SAS - ZA La Croix Rouge - 35530 Brécé - FRANCE

DON'T FORGET

Protect your slats further from UVs & dirt with the Ivernea winter shift or the Ivernea Plus 4-season protective shift.



VISIT OUR WEBSITE WWW.DEL-PISCINE.FR/EN

FOR MORE INFORMATION, PLEASE ASK YOUR POOL EXPERT

DEL SAS with a capital of 2 300 000 € - RCS 303355671 Rennes - ZA La Croix Rouge - 35530 Brécé - FRANCE • Printed by Calligraphy Print - 35220 Châteaubourg - FRANCE • Non-binding document • © DEL SAS • 01/25 • Do not throw away A-DBRO1200.L1

